

MEPL[®]

*The Easy Solution
for Fixing
Tiles and Stones*

**PRESENTING MEPL TILE
AND STONE ADHESIVE**

Adhesives | Epoxy Grout

TILE ADHESIVE (305)

DESCRIPTION : The ultimate one step single component thin set mortar for interior and exterior installation of ceramic & vitrified tiles.

APPLICATION : Can be used for interior and exterior application on floor and over masonry, concrete, mortar beds, cement plaster and tile on tile.

PACKING : 20 kg Bags.

COVERAGE : Approximately 50 to 55 sq.ft. per 20 kg bag at 6mm thickness.

COLOUR : Grey

NOTE : Coverage is based on smoothness and evenness of the substrate.

For improved performance in interior and exterior mixed with MEPL BOLD LATEX.



TILE ADHESIVE (315)

DESCRIPTION : It is multi purpose, polymer based thin set powder offering vast utility including application for floor & wall in interior and exterior area. installation of ceramic & vitrified tiles.

APPLICATION : Designed specially for interior and exterior floor & walls installations of all type of ceramic & verified tiles.

PACKING : 20kgs Bag.

COVERAGE : Approximately 50 to 55 sq.ft. per 20 kg bag at 6mm thickness.

COLOUR : Grey

NOTE : Coverage is based on smoothness and evenness of the substrate.

For improved performance in interior and exterior mixed with MEPL BOLD LATEX.



TILE ADHESIVE (325 HIGH FLEX)

DESCRIPTION : It is a single Component adhesive i.e. functional for high resistance laying of ceramic tiles, Marble & Homogeneous tiles. The tacking polymers provide deformability and fine finishing of the material affixed.

APPLICATION : Specially designed for interior and exterior floor and wall installation of all types of ceramic, vitrified tiles & natural stones.

PACKING : 20 kgs bag.

COVERAGE : Approximately 50 to 55 sq.ft. per 20 kg bag at 6mm thickness.

COLOUR : White / Grey

NOTE : Coverage is based on smoothness and evenness of the substrate.

For improved performance in interior and exterior mixed with MEPL BOLD LATEX.



AAC BLOCK ADHESIVE

DESCRIPTION : AAC Block Jointing Adhesive is a ready to mix, self-curing cementitious mortar for laying of AAC, CLC, Hollow concrete blocks and bricks.

APPLICATION : Concrete blocks, cement mortar blocks, bricks, concrete hollow blocks, aerated light weight blocks and fly ash bricks.

PACKAGING : 40 kgs bags. | **COLOUR :** Grey

COVERAGE : Approximately 220 to 240 sq ft per 40kg bag when used at 2mm bed thickness.

NOTE : Coverage is based on smoothness and evenness of the substrate depend upon size of the block.

For improved performance mixed with MEPL BOLD LATEX.



BOND LATEX (SBR Latex for Repairs & Waterproofing)

DESCRIPTION : Bond Latex is based on modified styrene butadiene latex. It is used for high performance application in water proofing and repairs it provides excellent bonding strength to concrete masonry stone work plaster & most of the building materials.

APPLICATION : Bond coating plaster to plaster, concrete to concrete, plaster to concrete, masonry to stone work and for palstering over brick masonry bonding coat and mortar for tiles and panels .

PACKAGING : 1 & 5 kg .



GROUT AD MIX

DESCRIPTION : GROUT AD-MIX is specially designed latex to Use in place of water, to improves the performance of Portland cement grouts.

APPLICATION: Designed for interior and exterior floor and wall joints of all types of ceramic tile, vitrified tiles and natural stone installation.

PACKING: 200 ML



TILE GROUT (UNSANDED)

DESCRIPTION : A carefully prepared blend of portland cement, graded aggregates, polymer based and colour - fast pigments. It is designed for joint width 1mm to 3mm width. For improved performance mixed with MEPL GROUT AD-MIX.

APPLICATION : Designed for joint filling width 1mm to 3mm. Specially for floor & walls of all type of ceramic, vitrified tiles, natural stones, granite stone.

PACKING : 1kg.

COLOUR : Available in range of more than 20 colours.



TILE GROUT EPOXY (EP-100)

DESCRIPTION : EP-100 Epoxy grout is stain free grout for floor and walls, colour fast, chemical resistance, 100% solid epoxy grout. Suitable for ceramic, vitrified tiles, marble and natural stones.

APPLICATION :

- Especially in stain prone areas, such as kitchens.
- Washrooms.
- Residential and commercial installations.
- Swimming pools.
- Fountains.
- Water bodies.
- Restaurants.
- Hospitals, etc.

COVERAGE : Varies with tile size and grout width.

PACKING : 1 & 5 kgs.

COLOUR : Available in a range of more than 20 colours.

Factory proportioned unit consisting of three conveniently packed components.

Hardener, resin and coloured filler powder.



TILE GROUT & EPOXY GROUT COLOUR SHADES

	901 Bright White		908 Midnight Black		915 Sierra Sunrise
	902 Quarry Red		909 Blue		916 Slate Grey
	903 Almond		910 Alpine Blue		917 Terracotta
	904 Coffee		911 Light Green		918 Pink
	905 Dark Green		912 Cream		919 Yellow
	906 Smoke Grey		913 Brown		920 Ivory
	907 Marble Beige		914 Chocolate		921 Sky Blue

• All Shades shown above are for indicative purpose and guidance only. • Verify actual appearance and compatibility with a test area before installation commences. • Actual shades and texture will depend on job site conditions. • Actual colour may vary, this is due to the fact that every computer monitor has a different capability to display colours.

Disclaimer : The product Information and application details given by the company and its representatives only as a general guide lines during usage. Users are advised to carry out tests & trials to ensure their product requirements prior to full scale usage of our product. We do not accept the responsibility for the misuse of our products. Various factors like temperature, weather, amount of water, skill of applicator used contribute to the performance of the product over which we have no control. We assure no warranty for finished work.

Mayureshwar Enterprises Private Limited

Regd Office: Shop B4, Balaji Complex, Syno. 663,
Shamshabad, Ranga Reddy Dist,
Telangana-501218 | Phone No. : 9505099930
Email : meplchemicals@gmail.com
www.meplchemicals.com

